

2019 MODEL YEAR JAGUAR E-PACE TECHNICAL SPECIFICATIONS	D150 2WD Manual	D150 AWD Manual	D150 AWD Automatic	D180 AWD Manual	D180 AWD Automatic	D240 AWD Automatic	P200 AWD Automatic	P250 AWD Automatic	P300 AWD Automatic	
Engine type	Inline-4 common rail diesel, 16 valves; DOHC; variable intake cam timing, variable geometry turbo	Inline-4 common rail diesel, 16 valves; DOHC; variable intake cam timing, variable geometry turbo	Inline-4 common rail diesel, 16 valves; DOHC; variable intake cam timing, variable geometry turbo	Inline-4 common rail diesel, 16 valves; DOHC; variable intake cam timing, variable geometry turbo	Inline-4 common rail diesel, 16 valves; DOHC; variable intake cam timing, variable geometry turbo	Inline-4 common rail diesel, 16 valves; DOHC; variable intake cam timing, variable geometry turbo	Inline-4 common rail diesel, 16 valves; DOHC; variable intake cam timing, variable geometry turbo	Inline-4 gasoline, 16 valve; DOHC, variable intake and exhaust cam timing; variable intake valve lift, twin-scroll turbo	Inline-4 gasoline, 16 valve; DOHC, variable intake and exhaust cam timing; variable intake valve lift, twin-scroll turbo	Inline-4 gasoline, 16 valve; DOHC, variable intake and exhaust cam timing; variable intake valve lift, twin-scroll turbo
Displacement	1999	1999	1999	1999	1999	1999	1999	1998	1998	1998
Bore / Stroke	83/92.3	83/92.3	83/92.3	83/92.3	83/92.3	83/92.3	83/92.3	83/92.3	83/92.3	83/92.3
Compression ratio	15.5:1	15.5:1	15.5:1	15.5:1	15.5:1	15.34:1	10.5 +/- 0.5:1	10.5 +/- 0.5:1	10.5 +/- 0.5:1	10.5 +/- 0.5:1
Max Power	150PS (110kW) @ 3500rpm	150PS (110kW) @ 3500rpm	150PS (110kW) @ 3500rpm	180PS (132kW) @ 4000rpm	180PS (132kW) @ 4000rpm	240PS (177kW) @ 4000rpm	200PS (146kW) @ 5500rpm	249PS (183kW) @ 5500rpm	300PS (221kW) @ 5500rpm	300PS (221kW) @ 5500rpm
Max Torque	380Nm (280lb ft) @ 1750rpm	380Nm (280lb ft) @ 1750rpm	380Nm (280lb ft) @ 1750rpm	430Nm (317lb ft) @ 1750rpm	430Nm (317lb ft) @ 1750rpm	500Nm (368lb ft) @ 1500rpm	340Nm (236lb ft) @ 1250rpm	365Nm (269lb ft) @ 1200-4500rpm	400Nm (295lb ft) @ 1500-4500rpm	400Nm (295lb ft) @ 1500-4500rpm
Euro standard	EU6	EU6	EU6	EU6	EU6	EU6	EU6	EU5	EU5	EU5
Transmission	Six-speed (manual)	Six-speed (manual)	Nine-speed (automatic)	Six-speed (manual)	Nine-speed (automatic)	Nine-speed (automatic)	Nine-speed (automatic)	Nine-speed (automatic)	Nine-speed (automatic)	Nine-speed (automatic)
1st (High / Low)	3.818	3.818	4.713	3.818	4.713	4.713	4.713	4.713	4.713	4.713
2nd (High / Low)	1.923	1.923	2.842	1.923	2.842	2.842	2.842	2.842	2.842	2.842
3rd (High / Low)	1.218	1.218	1.909	1.218	1.909	1.909	1.909	1.909	1.909	1.909
4th (High / Low)	0.880	0.880	1.382	0.880	1.382	1.382	1.382	1.382	1.382	1.382
5th (High / Low)	0.809	0.809	1.000	0.809	1.000	1.000	1.000	1.000	1.000	1.000
6th (High / Low)	0.673	0.673	0.808	0.673	0.808	0.808	0.808	0.808	0.808	0.808
7th (High / Low)	-	-	0.699	-	0.699	0.699	0.699	0.699	0.699	0.699
8th (High / Low)	-	-	0.580	-	0.580	0.580	0.580	0.580	0.580	0.580
9th (High / Low)	-	-	0.480	-	0.480	0.480	0.480	0.480	0.480	0.480
Reverse (High / Low)	4.139	4.139	3.830	4.139	3.830	3.830	3.830	3.830	3.830	3.830
Final drive ratio	3.238	3.238	3.944	3.238	3.944	3.944	4.544	4.544	4.544	4.544
Fuel tank capacity (litres) (usable)	55.7	55.7	55.7	55.7	55.7	55.7	68.5	68.5	68.5	68.5
AdBlue tank capacity (litres)	16	16	16	16	16	16	-	-	-	-
Brakes	Front: 325mm ventilated Rear: 300mm solid	Front: 325mm ventilated Rear: 300mm solid	Front: 325mm ventilated Rear: 300mm solid	Front: 325mm ventilated Rear: 300mm solid	Front: 325mm ventilated Rear: 300mm solid	Front: 325mm ventilated Rear: 300mm solid	Front: 349mm ventilated Rear: 300mm solid	Front: 325mm ventilated Rear: 300mm solid	Front: 325mm (17") 349mm (18-21") Rear: 300mm solid	Front: 349mm ventilated Rear: 300mm solid
Steering	Electronic Power Assisted Steering (EPAS) rack and pinion									
Four-wheel drive system	Standard Driveline - Torque on demand to rear axle Active Driveline - FWD or Torque on demand to rear axle									
Front suspension	MacPherson strut with lower control arm, coil springs, passive dampers and passive anti-roll bar									
Rear suspension	Integral multi-link suspension with coil springs, passive dampers and passive anti-roll bar									
WHEELS AND TYRES										
Wheels	7.0J x 17" 8.0J x 18" 8.0J x 19" 8.0J x 20"	7.0J x 17" 8.0J x 18" 8.0J x 19" 8.0J x 20"	7.0J x 17" 8.0J x 18" 8.0J x 19" 8.0J x 20"	7.0J x 17" 8.0J x 18" 8.0J x 19" 8.0J x 20" 8.0J x 21"	7.0J x 17" 8.0J x 18" 8.0J x 19" 8.0J x 20" 8.0J x 21"	7.0J x 17" 8.0J x 18" 8.0J x 19" 8.0J x 20" 8.0J x 21"	7.0J x 17" 8.0J x 18" 8.0J x 19" 8.0J x 20" 8.0J x 21"	7.0J x 17" 8.0J x 18" 8.0J x 19" 8.0J x 20" 8.0J x 21"	7.0J x 17" 8.0J x 18" 8.0J x 19" 8.0J x 20" 8.0J x 21"	7.0J x 17" 8.0J x 18" 8.0J x 19" 8.0J x 20" 8.0J x 21"
Tyres	225/65 R17 235/65 R17 235/60 R18 235/55 R19 245/45 R20	225/65 R17 235/65 R17 235/60 R18 235/55 R19 245/45 R20	225/65 R17 235/65 R17 235/60 R18 235/55 R19 245/45 R20	225/65 R17 235/65 R17 235/60 R18 235/55 R19 245/45 R20 245/45 R21	225/65 R17 235/65 R17 235/60 R18 235/55 R19 245/45 R20 245/45 R21	225/65 R17 235/65 R17 235/60 R18 235/55 R19 245/45 R20 245/45 R21	225/65 R17 235/65 R17 235/60 R18 235/55 R19 245/45 R20 245/45 R21	225/65 R17 235/65 R17 235/60 R18 235/55 R19 245/45 R20 245/45 R21	225/65 R17 235/65 R17 235/60 R18 235/55 R19 245/45 R20 245/45 R21	225/65 R17 235/65 R17 235/60 R18 235/55 R19 245/45 R20 245/45 R21
EXTERIOR DIMENSIONS										
Overall length (mm)						4395				
Overall height (mm)						1649				
Overall width (mirrors folded) (mm)						1984				
Overall width (mirrors out) (mm)						2088				
Wheelbase (mm)						2681				
Front overhang (mm)						882				
Rear overhang (mm)						832				
Front track (mm)						1625				
Rear track (mm)						1624				
Turning Circle - kerb-to-kerb (metres)						11.46				
Turning Circle - lock-to-lock						2.31				
Drag coefficient (Cd)	0.325	0.325	0.325	0.325	0.325	0.33	0.33	0.33	0.34	
INTERIOR DIMENSIONS										
Headroom (mm) *						Row 1: 996; Row 2: 970				
Shoulderroom (mm)						Row 1: 1425; Row 2: 1417				
Legroom (mm)						Row 1: 1018; Row 2: 892				
Centre console capacity (litres)						8.42 (5.94 with cup holders)				
Door bin capacity (litres)						Front: 10.56; Rear: 8.26				
Luggage capacity (litres)						Behind Row 1: 1234; Behind Row 2: 577				
Loadspace length (mm)						Behind Row 1: 1568; Behind Row 2: 806				
Loadspace height (mm)						748				
Loadspace width (mm)						1311 (1057 between wheel arches)				
Loadspace door aperture height (mm)						705				
Loadspace door aperture width (mm)						994				
Underfloor loadspace volume (litres)						93				
ALL-TERRAIN CAPABILITY										
Approach angle (deg) †						22.8				
Departure angle (deg) †						29.4				
Ramp breakover angle (deg) †						21.1				
Wading depth (mm)						500				
Ground clearance (mm)						204				
Maximum ascent / descent gradient (deg)						45				
Maximum side slope traverse gradient (deg)						35				
TOWING CAPABILITY										
Maximum permissible towable mass (kg)	750	750	750	750	750	750	750	750	750	750
Maximum permissible unbraked towable mass (kg)	1600	1800	1800	1800	1800	1800	1800	1800	1800	1800
PERFORMANCE										
0-60mph (0-97km/h) (secs)	9.5	10.1	9.9	9.4	8.6	6.8	7.7	6.7	6.1	6.1
0-62mph (0-100km/h) (secs)	10.1	10.7	10.5	9.9	9.1	7.4	8.2	7.1	6.5	6.5
Top speed (km/h / mph)	199 / 124	194 / 120	193 / 120	207 / 128	205 / 127	224 / 139	216 / 134	230 / 143	243 / 151	243 / 151
Fuel consumption (l/100km / mpg)										
NEDC equivalent combined * (class 2 tyre)	5.5 (51.4)	5.6 (50.4)	6.1 (46.3)	5.7 (49.6)	6.1 (46.3)	6.8 (41.5)	8.1 (34.9)	8.3 (34.0)	8.9 (31.7)	8.9 (31.7)
CO ₂ emissions (g/km)										
NEDC equivalent combined * (class 2 tyre)	146	148	162	150	162	178	186	189	203	203
WEIGHT										
EU unladen	1775	1831	1843	1831	1843	1926	1832	1832	1894	1894
EU DIN	1700	1756	1768	1756	1768	1851	1757	1757	1819	1819