


### 4.4L SDV8 Diesel



Height mm (in)	1780 (70.1)	Four wheel drive system	Permanent 4 wheel drive with standard locking centre differential & Terrain Response TM2, optional locking rear axle differential.
Width excl. wing mirrors / wing mirrors folded mm (in)	1983 (78.1) / 2220 (87.4)	Engine type	Longitudinal / V8 / 32-valve
Length mm (in)	4850 (191)	Displacement cc (cu.in)	4367 (266.5)
Wheelbase mm (in)	2923 (115.1)	Bore / Stroke mm (in)	84.0 (3.30) / 98.5 (3.88)
Approach angle deg	33.0 (off-road height)	Compression ratio: 1	16.1
Departure angle deg	31.0 (off-road height)	Max Power PS (kW)	339 (250)
Ramp breakover angle deg	27.3 (off-road height)	Max Torque Nm (lb ft)	700
Wading depth mm (in)	850 (33.5)	Transmission	ZF 8HP70
Turning circle m (ft)	12.5 (41.0)	Emissions	EU5
Drag coefficient (Cd)	0.36	CO2 EU Combined	229
Weight from kg	2398	Fuel tank capacity litres	105
Front suspension	SLA suspension with twin lower links with air springs/CVD with Passive ARB or optional ARC	Fuel consumption EU5 urban/extra urban/combined L/100km (mpg)	11.5 (24.6) / 7.6 (37.2) / 8.7 (32.5)
Rear suspension	Integral link suspension with air springs/ CVD with Passive ARB or optional ARC	0-60 mph	6.5
Brakes	380 mm ventilated disc-front / 365 mm ventilated disc-rear	0-100 km/h	6.9
Steering	Electric Power Assisted Steering (EPAS) rack and pinion	Top speed mph	130 (210) / 140 (225) opt Dynamic pack