

## Range Rover Evoque Technical Data

	5-Door						Coupé					
	eD4 2.2L manual 2WD	TD4 2.2L manual 4WD	TD4 2.2L auto 4WD	SD4 2.2L manual 4WD	SD4 2.2L auto 4WD	Si4 2.0L petrol auto 4WD	eD4 2.2L manual 2WD	TD4 2.2L manual 4WD	TD4 2.2L auto 4WD	SD4 2.2L manual 4WD	SD4 2.2L auto 4WD	Si4 2.0L petrol auto 4WD
Height mm (in)	1635 (64.4)						1605 (63.2)					
Width mm (in)	1965 (77.4)						1965 (77.4)					
Length mm (in)	4355 (171.5) / 4365 (171.9) Dynamic derivative						4355 (171.5) / 4365 (171.9) Dynamic derivative					
Wheelbase mm (in)	2660 (104.8)						2660 (104.8)					
Turning Circle m (ft)	11.3 (37.1)						11.3 (37.1)					
Drag coefficient from... Cd	0.35						0.36					
Weight from... kg	1625	1700	1715	1700	1715	1670	1595	1670	1685	1670	1685	1640
Front suspension	Macpherson strut with lower control arm and anti-roll bar						Macpherson strut with lower control arm and anti-roll bar					
Rear suspension	Strut assembly with lateral and longitudinal links and anti-roll bar						Strut assembly with lateral and longitudinal links and anti-roll bar					
Brakes	300mm ventilated disc front / 302mm solid disc rear						300mm ventilated disc front / 302mm solid disc rear					
Steering	Electric power assisted rack and pinion						Electric power assisted rack and pinion					
Wheel drive system	Front Wheel Drive	Full time 4 wheel drive with Haldex rear axle differential	Full time 4 wheel drive with Haldex rear axle differential	Full time 4 wheel drive with Haldex rear axle differential	Full time 4 wheel drive with Haldex rear axle differential	Full time 4 wheel drive with Haldex rear axle differential	Front Wheel Drive	Full time 4 wheel drive with Haldex rear axle differential	Full time 4 wheel drive with Haldex rear axle differential	Full time 4 wheel drive with Haldex rear axle differential	Full time 4 wheel drive with Haldex rear axle differential	Full time 4 wheel drive with Haldex rear axle differential
Engine type	Transverse, in-line 4-cylinder, 16-valve turbo diesel, common rail fuel injection	Transverse, in-line 4-cylinder, 16-valve turbo diesel, common rail fuel injection	Transverse, in-line 4-cylinder, 16-valve turbo diesel, common rail fuel injection	Transverse, in-line 4-cylinder, 16-valve turbo diesel, common rail fuel injection	Transverse, in-line 4-cylinder, 16-valve turbo diesel, common rail fuel injection	Transverse, in-line 4-cylinder, 16-valve turbo diesel, common rail fuel injection	Transverse, in-line 4-cylinder, 16-valve turbo diesel, common rail fuel injection	Transverse, in-line 4-cylinder, 16-valve turbo diesel, common rail fuel injection	Transverse, in-line 4-cylinder, 16-valve turbo diesel, common rail fuel injection	Transverse, in-line 4-cylinder, 16-valve turbo diesel, common rail fuel injection	Transverse, in-line 4-cylinder, 16-valve turbo diesel, common rail fuel injection	Transverse, in-line 4-cylinder, 16-valve turbo diesel, common rail fuel injection
Displacement cc	2179	2179	2179	2179	2179	1999	2179	2179	2179	2179	2179	1999
Bore / Stroke mm (in)	85 / 96 (3.35 / 3.80)	85 / 96 (3.35 / 3.80)	85 / 96 (3.35 / 3.80)	85 / 96 (3.35 / 3.80)	85 / 96 (3.35 / 3.80)	87.5 / 83.1 (3.45 / 3.27)	85 / 96 (3.35 / 3.80)	85 / 96 (3.35 / 3.80)	85 / 96 (3.35 / 3.80)	85 / 96 (3.35 / 3.80)	85 / 96 (3.35 / 3.80)	87.5 / 83.1 (3.45 / 3.27)
Compression ratio :1	15.8	15.8	15.8	15.8	15.8	10.0	15.8	15.8	15.8	15.8	15.8	10.0
Max Power PS (kW)	150 (110)	150 (110)	150 (110)	190 (140)	190 (140)	240 (177)	150 (110)	150 (110)	150 (110)	190 (140)	190 (140)	240 (177)
Max Power US bhp	-	-	-	-	-	240	-	-	-	-	-	240
Max Torque Nm (lb ft)	380 (280)	400 (295)	400 (295)	420 (310)	420 (310)	340 (251)	380 (280)	400 (295)	400 (295)	420 (310)	420 (310)	340 (251)
Fuel consumption EU5 urban/extra urban/combined L/100km (mpg)	6.0 (47.1) / 4.5 (62.8) / 5.0 (56.5)	6.7 (42.2) / 5.2 (54.3) / 5.7 (49.6)	7.9 (35.8) / 5.7 (49.6) / 6.5 (43.5)	6.7 (42.2) / 5.2 (54.3) / 5.7 (49.6)	7.9 (35.8) / 5.7 (49.6) / 6.5 (43.5)	11.9 (23.7) / 6.9 (40.9) / 8.7 (32.5)	5.9 (47.9) / 4.5 (62.8) / 4.9 (57.6)	6.7 (42.2) / 5.2 (54.3) / 5.7 (49.6)	7.8 (36.2) / 5.7 (49.6) / 6.4 (44.1)	6.7 (42.2) / 5.2 (54.3) / 5.7 (49.6)	7.8 (36.2) / 5.7 (49.6) / 6.4 (44.1)	11.9 (23.7) / 6.9 (40.9) / 8.7 (32.5)
Emissions	EU5	EU5	EU5	EU5	EU5	EU5	EU5	EU5	EU5	EU5	EU5	EU5
CO <sub>2</sub> g/km combined	133	149	174	149	149	199	129	149	169	149	169	199
Transmission	M66 EH50 6-speed manual	Getrag M66 6-speed manual	Aisin AW F21 6-speed auto	Getrag M66 6-speed manual	Aisin AW F21 6-speed auto	Aisin AW F21 6-speed auto	M66 EH50 6-speed manual	Getrag M66 6-speed manual	Aisin AW F21 6-speed auto	Getrag M66 6-speed manual	Aisin AW F21 6-speed auto	Aisin AW F21 6-speed auto
Fuel tank capacity litres	60	60	60	60	60	70	60	60	60	60	60	70
Range EU combined miles (km)	720 (1160)	630 (1015)	555 (890)	630 (1015)	555 (890)	500 (805)	735 (1180)	630 (1015)	565 (905)	630 (1015)	565 (905)	500 (805)
0-60 mph	10.6	10.3	9.0	9.5	8.0	7.1	10.6	10.3	9.0	9.5	8.0	7.1
0-100 kph	11.2	10.8	9.6	10.0	8.5	7.6	11.2	10.8	9.6	10.0	8.5	7.6
Top speed mph (kph)	112 (180)	115 (185)	113 (182)	124 (200)	121 (195)	135 (217)	112 (180)	115 (185)	113 (182)	124 (200)	121 (195)	135 (217)

This is certified under EU5 legislation