

## 2011 Freelander 2 technical data

	<b>TD4 150PS manual 4WD</b>	<b>TD4 150PS auto 4WD</b>	<b>SD4 190PS auto 4WD</b>	<b>eD4 150PS manual 2WD</b>
<b>Height mm (in)</b>	1740 (68.5)	1740 (68.5)	1740 (68.5)	1740 (68.5)
<b>Width mm (in)</b>	2195 (86.5)	2195 (86.5)	2195 (86.5)	2195 (86.5)
<b>Length mm (in)</b>	4500 (177)	4500 (177)	4500 (177)	4500 (177)
<b>Wheelbase mm (in)</b>	2660 (104.7)	2660 (104.7)	2660 (104.7)	2660 (104.7)
<b>Turning Circle m (ft)</b>	11.3 (37)	11.3 (37)	11.3 (37)	11.3 (37)
<b>Min Weight from kg (lb)</b>	1785 (3935)	1805 (3979)	1805 (3979)	1710 (3770)
<b>Front suspension</b>	Macpherson strut with lower control arm and anti-roll bar	Macpherson strut with lower control arm and anti-roll bar	Macpherson strut with lower control arm and anti-roll bar	Macpherson strut with lower control arm and anti-roll bar
<b>Rear suspension</b>	Strut assembly with lateral and longitudinal links and anti-roll bar	Strut assembly with lateral and longitudinal links and anti-roll bar	Strut assembly with lateral and longitudinal links and anti-roll bar	Strut assembly with lateral and longitudinal links and anti-roll bar
<b>Brakes</b>	Ventilated front disc - 300mm, solid rear – 302mm	Ventilated front disc - 300mm, solid rear – 302mm	Ventilated front disc - 300mm, solid rear – 302mm	Ventilated front disc - 300mm, solid rear – 302mm
<b>Steering</b>	Hydraulic power assisted rack and pinion	Hydraulic power assisted rack and pinion	Hydraulic power assisted rack and pinion	Hydraulic power assisted rack and pinion
<b>Four Wheel-Drive system</b>	Full time 4 wheel drive with Haldex rear axle differential.	Full time 4 wheel drive with Haldex rear axle differential.	Full time 4 wheel drive with Haldex rear axle differential.	Front wheel-drive
<b>Engine type</b>	Transverse, in-line 4-cylinder, 16-valve turbo diesel, common rail fuel injection	Transverse, in-line 4-cylinder, 16-valve turbo diesel, common rail fuel injection	Transverse, in-line 4-cylinder, 16-valve turbo diesel, common rail fuel injection	Transverse, in-line 4-cylinder, 16-valve turbo diesel, common rail fuel injection
<b>Displacement cc</b>	2179cc	2179cc	2179	2179cc
<b>Bore/stroke mm (in)</b>	85x96	85x96	85x96	85x96
<b>Compression ratio</b>	15.8:1	15.8:1	15.8:1	15.8:1
<b>Max power PS (kW)</b>	150 (110)	150 (110)	190 (140)	150 (110)
<b>Max Torque Nm (lb ft)</b>	420 (310)	420 (310)	420 (310)	420 (310)
<b>Fuel consumption EU urban/extra urban/combined (mpg-L/100km)</b>	38.2/50.4/45.6 (7.4/5.6/6.2)	32.5/49.6/40.4 (8.7/5.7/7.0)	32.5/49.6/40.4 (8.7/5.7/7.0)	39.6/52.2/47.2 (7.1/5.4/6.0*) (*manufacturers estimate)
<b>Emissions</b>	EU5	EU5	EU5	EU5
<b>CO<sub>2</sub> g/km</b>	165	185	185	158
<b>Transmission</b>	M66 EH50 6-speed manual	Aisin SWF21 6 Speed auto	Aisin SWF21 6 Speed auto	M66 EH50 6-speed manual
<b>Fuel tank capacity</b>	68/15/18	68/15/18	68/15/18	68/15/18

<b>litres/imp gals/US gals</b>				
<b>Range, miles (km)</b>	680 (1095)	600 (970)	600 (970)	710 (1141)
<b>0-60mph</b>	10.9	10.5	8.7	10.9
<b>Top speed mph (kph)</b>	112/181	112/181	118/190	112/181