

The 2013 Range Rover Evoque

Technical Data – Canada and US

(All numbers are preliminary manufacturer estimates)

	5-Door	Coupe
Engine	Transverse, inline 4-cylinder, variable valve timing, gasoline, direct injection, turbocharged with Bosch Engine Management System	
Displacement cc	1999	
Bore/stroke mm (in)	87.5 / 83.1 (3.45 / 3.27)	
Compression ratio	10.0:1	
Max Horsepower	240 hp @ 5,500 RPM	
Max Torque	250 lb-ft @ 1,750 RPM	
Transmission	6-speed automatic Aisin AW F21	
Gear Ratios	Forward (1-6) 4.148, 2.370, 1.556, 1.155, 0.859, 0.686 Reverse: 3.394 Primary Transfer Ratio: 1.452 (Single Speed) Differential/Axle Ratio: 2.583 Final Drive Ratio (Differential X Primary): 3.75	
Drive system	Full-time four-Wheel drive with Haldex rear axle differential; Terrain Response system	
Front suspension	Macpherson strut with lower control arm and anti-roll bar	
Rear suspension	Strut assembly with lateral and longitudinal links and anti-roll bar	
Brakes – Type and Diameter	Four-wheel Disc (11.8" front, 11.9" Rear) Electronic Parking Brake Contained in Rear Calipers	
Wheel and Tire Size	235/55R19 (V Rated) on 8.0Jx19" wheel (Optional) 245/45R20 (V Rated) on 8.0Jx20" wheel	
Steering	Electric power assisted rack and pinion	
Turning Circle – ft. (m)	37.1 (11.3)	
Turns lock-to-lock	2.47	
Overall Steering Ratio (On Centre)	15.4	
Turning Circle – ft. (m)	37.1 (11.3)	
Exterior Dimensions		
Drag Coefficient	0.35	0.36
Wheelbase - inches (mm)	104.8 (2660)	
Length - inches (mm)	171.5 (4355) (Pure & Prestige) 171.9 (4365) (Dynamic)	
Width - inches (mm), mirrors folded	77.4 (1965)	
Width - inches (mm) with mirrors	83.7 (2125)	
Height - inches (mm)	64.4 (1635)	63.2 (1605)
Front wheel track- inches (mm)	63.9 (1625)	
Rear wheel track- inches (mm)	64.1 (1630)	
Minimum ground clearance inches (mm)	8.3 (212)	
Front axle ground clearance - inches (mm)	8.4 (215)	
Rear axle ground clearance - inches (mm)	9.5 (240)	
Maximum water wading depth - inches (mm)	19.7 (500)	
Maximum operating tilt angles	30 degrees continuous 45 degrees momentary	

Curb weight – lbs. (kg)	3902 (1770)	
Off-road geometry	Approach Angle 25° (19° Dynamic) Ramp Angle 22° Departure Angle 33° (30° Dynamic)	
Towing Capacity – lbs. (kg)	3500 (1585) Tongue Weight – 330 (150)	
Interior Dimensions		
Front headroom- inches (mm)	40.3(1025)	39.1 (995)
Front legroom inches (mm)	40.1 (1020) SAE L34	
Front shoulder room inches (mm)	56.6 (1435)	
Rear headroom- inches (mm)	39.7 (1010)	38.2 (970)
Rear legroom- inches (mm)	36.4 (925)	35.7 (905)
Rear shoulder room inches (mm)	55.4 (1405)	53.2 (1350)
Luggage capacity length - inches (mm)	62.2 (1582) Rear seats folded forward 31.3 (796) Rear seats upright	
Luggage volume– cu.-ft. (litres)	51.0 (1445) Rear seats folded 20.3 (575) Rear seats upright	47.6 (1350) Rear seats folded 19.4 (550) Rear seats upright
Performance and Efficiency		
0-60 mph ⁵	7.1 seconds	
0-100 kph ⁵	7.6 seconds	
Top track speed mph (kph)	135 (217)	
Estimated Fuel Economy ⁴	Highway 7.1 L/100km, city 10.6L/100km and combined 9.0 L/100km ⁴	
Fuel tank capacity US gals/litres	18.5 (70)	

Footnotes

[1] These figures are correct at time of going to press. All figures are fuel economy estimates.

[2] Please consult your dealer for details of changes associated with option format. Weights reflect vehicles to standard specifications. Option features increase weight.