

2018 MODEL YEAR JAGUAR E-PACE TECHNICAL SPECIFICATIONS	D150 2WD Manual	D150 AWD Manual	D150 AWD Automatic	D180 AWD Manual	D180 AWD Automatic	D240 AWD Automatic	P250 AWD Automatic	P300 AWD Automatic	
Engine type	Inline-4 common rail diesel, 16 valves; DOHC; variable intake cam timing, variable geometry turbo	Inline-4 common rail diesel, 16 valves; DOHC; variable intake cam timing, variable geometry turbo	Inline-4 common rail diesel, 16 valves; DOHC; variable intake cam timing, variable geometry turbo	Inline-4 common rail diesel, 16 valves; DOHC; variable intake cam timing, variable geometry turbo	Inline-4 common rail diesel, 16 valves; DOHC; variable intake cam timing, variable geometry turbo	Inline-4 common rail diesel, 16 valves; DOHC; variable intake cam timing, variable geometry turbo	Inline-4 gasoline, 16 valve; DOHC, variable intake and exhaust cam timing; variable intake valve lift, twin-scroll turbo	Inline-4 gasoline, 16 valve; DOHC, variable intake and exhaust cam timing; variable intake valve lift, twin-scroll turbo	
Displacement	1999	1999	1999	1999	1999	1999	1998	1998	
Bore / Stroke	83/92.3	83/92.3	83/92.3	83/92.3	83/92.3	83/92.3	83/92.3	83/92.3	
Compression ratio	15.5:1	15.5:1	15.5:1	15.5:1	15.5:1	15.34:1	10.5 +/- 0.5:1	10.5 +/- 0.5:1	
Max Power	150PS (110kW) @ 3500rpm	150PS (110kW) @ 3500rpm	150PS (110kW) @ 3500rpm	180PS (132kW) @ 4000rpm	180PS (132kW) @ 4000rpm	240PS (177kW) @ 4000rpm	249PS (183kW) @ 5500rpm	300PS (221kW) @ 5500rpm	
Max Torque	380Nm (280lb ft) @ 1750rpm	380Nm (280lb ft) @ 1750rpm	380Nm (280lb ft) @ 1750rpm	430Nm (317lb ft) @ 1750rpm	430Nm (317lb ft) @ 1750rpm	500Nm (368lb ft) @ 1500rpm	365Nm (269lb ft) @ 1200-4500rpm	400Nm (295lb ft) @ 1500-4500rpm	
Euro standard	EU6	EU6	EU6	EU6	EU6	EU6	EU5	EU5	
Transmission	Six-speed (manual)	Six-speed (manual)	Nine-speed (automatic)	Six-speed (manual)	Nine-speed (automatic)	Nine-speed (automatic)	Nine-speed (automatic)	Nine-speed (automatic)	
1st (High / Low)	3.818	3.818	4.713	3.818	4.713	4.713	4.713	4.713	
2nd (High / Low)	1.923	1.923	2.842	1.923	2.842	2.842	2.842	2.842	
3rd (High / Low)	1.218	1.218	1.909	1.218	1.909	1.909	1.909	1.909	
4th (High / Low)	0.880	0.880	1.382	0.880	1.382	1.382	1.382	1.382	
5th (High / Low)	0.809	0.809	1.000	0.809	1.000	1.000	1.000	1.000	
6th (High / Low)	0.673	0.673	0.808	0.673	0.808	0.808	0.808	0.808	
7th (High / Low)	-	-	0.699	-	0.699	0.699	0.699	0.699	
8th (High / Low)	-	-	0.580	-	0.580	0.580	0.580	0.580	
9th (High / Low)	-	-	0.480	-	0.480	0.480	0.480	0.480	
Reverse (High / Low)	4.139	4.139	3.830	4.139	3.830	3.830	3.830	3.830	
Final drive ratio	3.238	3.238	3.944	3.238	3.944	3.944	4.544	4.544	
Fuel tank capacity (litres) (usable)	55.7	55.7	55.7	55.7	55.7	55.7	68.5	68.5	
AdBlue tank capacity (litres)	16	16	16	16	16	16			
Brakes	Front: 325mm ventilated Rear: 300mm solid	Front: 325mm ventilated Rear: 300mm solid	Front: 325mm ventilated Rear: 300mm solid	Front: 325mm ventilated Rear: 300mm solid	Front: 325mm ventilated Rear: 300mm solid	Front: 349mm ventilated Rear: 300mm solid	Front: 325mm (17") 349mm (18-21") Rear: 300mm solid	Front: 349mm ventilated Rear: 300mm solid	
Steering	Electronic Power Assisted Steering (EPAS) rack and pinion								
Four-wheel drive system	Standard Driveline - Torque on demand to rear axle Active Driveline - FWD or Torque on demand to rear axle								
Front suspension	MacPherson strut with lower control arm, coil springs, passive dampers and passive anti-roll bar								
Rear suspension	Integral multi-link suspension with coil springs, passive dampers and passive anti-roll bar								
WHEELS AND TYRES									
Wheels	7.0J x 17" 8.0J x 18" 8.0J x 19" 8.0J x 20"	7.0J x 17" 8.0J x 18" 8.0J x 19" 8.0J x 20"	7.0J x 17" 8.0J x 18" 8.0J x 19" 8.0J x 20"	7.0J x 17" 8.0J x 18" 8.0J x 19" 8.0J x 20" 8.0J x 21"	7.0J x 17" 8.0J x 18" 8.0J x 19" 8.0J x 20" 8.0J x 21"	7.0J x 17" 8.0J x 18" 8.0J x 19" 8.0J x 20" 8.0J x 21"	7.0J x 17" 8.0J x 18" 8.0J x 19" 8.0J x 20" 8.0J x 21"	7.0J x 17" 8.0J x 18" 8.0J x 19" 8.0J x 20" 8.0J x 21"	7.0J x 17" 8.0J x 18" 8.0J x 19" 8.0J x 20" 8.0J x 21"
Tyres	225/65 R17 235/65 R17 235/60 R18 235/55 R19 245/45 R20	225/65 R17 235/65 R17 235/60 R18 235/55 R19 245/45 R20	225/65 R17 235/65 R17 235/60 R18 235/55 R19 245/45 R20	225/65 R17 235/65 R17 235/60 R18 235/55 R19 245/45 R20 245/45 R21	225/65 R17 235/65 R17 235/60 R18 235/55 R19 245/45 R20 245/45 R21	225/65 R17 235/65 R17 235/60 R18 235/55 R19 245/45 R20 245/45 R21	225/65 R17 235/65 R17 235/60 R18 235/55 R19 245/45 R20 245/45 R21	225/65 R17 235/65 R17 235/60 R18 235/55 R19 245/45 R20 245/45 R21	225/65 R17 235/65 R17 235/60 R18 235/55 R19 245/45 R20 245/45 R21
EXTERIOR DIMENSIONS									
Overall length (mm)	4395								
Overall height (mm)	1649								
Overall width (mirrors folded) (mm)	1984								
Overall width (mirrors out) (mm)	2088								
Wheelbase (mm)	2681								
Front overhang (mm)	882								
Rear overhang (mm)	832								
Front track (mm)	1625								
Rear track (mm)	1624								
Turning Circle - kerb-to-kerb (metres)	11.46								
Turning Circle - lock-to-lock	2.31								
Drag coefficient (Cd)	0.325	0.325	0.325	0.325	0.325	0.34	0.34	0.36	
INTERIOR DIMENSIONS									
Headroom (mm) *	Row 1: 996; Row 2: 970								
Shoulderroom (mm)	Row 1: 1425; Row 2: 1417								
Legroom (mm)	Row 1: 1018; Row 2: 892								
Centre console capacity (litres)	8.42 (5.94 with cup holders)								
Door bin capacity (litres)	Front: 10.56; Rear: 8.26								
Luggage capacity (litres)	Behind Row 1: 1234; Behind Row 2: 577								
Loadspace length (mm)	Behind Row 1: 1568; Behind Row 2: 806								
Loadspace height (mm)	748								
Loadspace width (mm)	1311 (1057 between wheel arches)								
Loadspace door aperture height (mm)	705								
Loadspace door aperture width (mm)	994								
Underfloor loadspace volume (litres)	93								
ALL-TERRAIN CAPABILITY									
Approach angle (deg) †	22.8								
Departure angle (deg) †	29.4								
Ramp breakover angle (deg) †	21.1								
Wading depth (mm)	500								
Ground clearance (mm)	204								
Maximum ascent / descent gradient (deg)	45								
Maximum side slope traverse gradient (deg)	35								
TOWING CAPABILITY									
Maximum permissible towable mass (kg)	750	750	750	750	750	750	750	750	
Maximum permissible unbraked towable mass (kg)	1600	1800	1800	1800	1800	1800	1800	1800	
PERFORMANCE									
0-60mph (0-97km/h) (secs)	9.5	10.1	9.9	9.4	8.7	7.0	6.6	5.9	
0-62mph (0-100km/h) (secs)	10.1	10.7	10.5	9.9	9.3	7.4	7.0	6.4	
Top speed (km/h / mph)	199 / 124	194 / 120	193 / 120	207 / 128	205 / 127	224 / 139	230 / 143	243 / 151	
Fuel consumption (EU urban)	50.4mpg (5.6l/100km) (17" wheel) 48.7mpg (5.8l/100km) (18-20" wheel)	47.1mpg (6.0l/100km)	43.5mpg (6.5l/100km)	47.1mpg (6.0l/100km)	43.5mpg (6.5l/100km)	39.2mpg (7.2l/100km)	29.7mpg (9.5l/100km)	29.1mpg (9.7l/100km)	
Fuel consumption (EU extra urban)	67.3mpg (4.2l/100km) (17" wheel) 64.2mpg (4.4l/100km) (18-20" wheel)	58.9mpg (4.8l/100km)	55.4mpg (5.1l/100km)	58.9mpg (4.8l/100km)	55.4mpg (5.1l/100km)	51.4mpg (5.5l/100km)	42.8mpg (6.6l/100km)	40.4mpg (7.0l/100km)	
Fuel consumption (EU combined)	60.1mpg (4.7l/100km) (17" wheel) 55.7mpg (4.9l/100km) (18-20" wheel)	54.3mpg (5.2l/100km)	50.4mpg (5.6l/100km)	54.3mpg (5.2l/100km)	50.4mpg (5.6l/100km)	45.6mpg (6.2l/100km)	36.7mpg (7.7l/100km)	35.3mpg (8.0l/100km)	
EU Combined CO ₂ (g/km)	124 (17" wheel) 129 (18-20" wheel)	137	147	137	147	162	174	181	
WEIGHT									
EU unladen	1775	1831	1843	1831	1843	1926	1832	1894	
EU DIN	1700	1756	1768	1756	1768	1851	1757	1819	